


Technical data



Technical data											
Model	Power (W)	Current (A)	Speed (rpm)	Flow (m³/h)	Pressure (Pa)	Efficiency (%)	Sound power level (dB)	Sound pressure level (dB)	Weight (kg)	Dimensions (mm)	Material
MF100	10	0.05	1400	10	10	0.8	65	65	0.1	100x100x40	ABS
MF150	15	0.07	1400	15	15	0.8	65	65	0.1	150x150x40	ABS
MF200	20	0.09	1400	20	20	0.8	65	65	0.1	200x200x40	ABS
MF250	25	0.11	1400	25	25	0.8	65	65	0.1	250x250x40	ABS
MF300	30	0.13	1400	30	30	0.8	65	65	0.1	300x300x40	ABS
MF350	35	0.15	1400	35	35	0.8	65	65	0.1	350x350x40	ABS
MF400	40	0.17	1400	40	40	0.8	65	65	0.1	400x400x40	ABS
MF450	45	0.19	1400	45	45	0.8	65	65	0.1	450x450x40	ABS
MF500	50	0.21	1400	50	50	0.8	65	65	0.1	500x500x40	ABS

How to apply the fan

Mounting

The fan is mounted on a wall or ceiling using the four screws provided. The fan must be installed in a well-ventilated area.

Wiring

The fan is connected to the power supply using the provided cable. The fan must be connected to a dedicated circuit with a fuse.

Maintenance

The fan should be cleaned regularly to ensure optimal performance. The fan should be inspected for damage and replaced if necessary.

The fan is designed for use in residential and commercial environments. It is not suitable for use in industrial environments with high humidity or corrosive gases.



www.elettrochimica.it

Recirculation fans

ELETTROCHIMICA FIBERE

Il prossimo livello di efficienza energetica senza

